

24" DEEP SLIDING GLASS DOOR **BACK BAR COOLER**

Project Name: _

Model #:__

Project Location:

___ Quantity: ____

Available Warehouse:_

EBB Series Model: EBB48G-SD



Refrigeration System

Side mounted, self-contained and fully detachable Blizzard R290 condensing unit uses environmentally friendly, EPA-compliant R290 refrigerant with zero (0) Ozone Depletion Potential (ODP) and three (3) Global Warming Potential (GWP). Blizzard R290 is easily replaceable and requires no on-site brazing.

- Electronically commutated (ECM) fan motors achieve rapid cooling with less energy consumption.
- Full-length air duct system ensures optimal circulation of cold air.
- · Time-initiated and temperature-terminated auto defrost cycle for seamless operation. · Large capacity, corrosion-resistant condenser and evaporator coils.

- Large capacity, convision-resistant condenser and evaporator colls.
 Self-maintaining, energy-efficient condensate drain pan requires no external drains or electric heaters.
 High performance, auto-reverse condenser fan motor supports compressor ventilation and condenser coil cleaning. Refer to owner's manual for full maintenance instructions.
 Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P.

Cabinet Construction

- Heavy duty stainless steel countertop with textured laminate, black vinyl exterior.
 Open spaced interior with no walls between compartments.
 Galvanized steel interior walls and high quality stainless steel floor.

- 1 3/4" thick high density polyurethane insulation.
- Built-in caster thread receptacles for all models.

Liahtina

· Shielded LED bar lighting with on/off switch provides bright, high color illumination at lower heat output.

Doors

- · Low emissivity double glass panes reflect UV rays for efficient cooling.
- Black PVC door frames.
- Self-closes by weight.
- Removable doors and stainless steel door tracks make cleaning an easy process.

Shelving

- · Two epoxy coated, steel wire shelves per section.
- · Height adjustable stainless steel clips.

Temperature Control

- · Multi-function digital controller with easy to read LED display.
- Factory preset temperature, 35°F.
 Temperature setting range from 33°F to 54°F.
- Audible overheat protection alarm for compressor and condenser coil.

Options

- · Additional shelving.
- 3" or 5" swivel casters with locks.
 3.5" 6" height-adjustable and interchangeable legs.



Please visit our website for updated Energy Efficiency information

Ref/		Capacity		Shelves Refrigerant	НР	Power	Amps	Crated	Exterior Dimensions				
Frz/Dual		Cu. Ft.	12 oz. Cans	12 oz. Bottle		nonigorunt		V-Hz-Ph	Allipo	Weight	L	D	H*
REF	2	13	420	294	4	R-290	1/4+	115-60-1	3.5	278 lbs (126kg)	49" (1245mm)	24.5" (622mm)	37.25" (946mm)

(†)Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). (►) Product capacity is calculated based on standard industry figures. (★) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.





24" DEEP SLIDING GLASS DOOR BACK BAR COOLER

EBB Series


s Model: EBB48G-SD

49" (1245mm)

DIMENSIONAL DATA


L


PLAN VIEW



FRONT

SIDE





Air

AIRFLOW

ACCESSORIES & OPTIONS

Part Number	Description			
Additional Shelving	Contact Everest Refrigeration for more information.			
AJL03-00	Interchangeable Leg for Caster (Optional)			
CASA3-01	3" Overall Height Caster Assembly - (2) Front (2) Rear			
CASA5-01	5" Overall Height Caster Assembly - (2) Front (2) Rear			

		()		
External Dimensions	D	24.5" (622mm)		
	H*	37.25" (946mm)		
Crated Weight		278 lbs. (126kg)		
Doors/Drawers/Lids		2		
Max Weight Support (LBS)	-		
STORAGE DATA				
Net Capacity Cu. Ft. 🏲		13		
Shelves		4		
Barrels		-		
20 oz. Bottles		-		
12 oz. Bottles		294		
12 oz. Cans		420		
8" Mugs		-		
# of Pans (Top)		-		
# of Pans (Drawer)		-		
Dividers		-		
Trays		-		

ELECTRICAL DATA

Voltage	115-60-1
Full Load Amperage	3.5A
Feed Wires with Ground	3
Cord Length	9ft
NEMA Plug Type	•• NEMA 5-15P

REFRIGERATION DATA

Compressor Mounting	Side
Refrigerant	R-290
Compressor HP	1/4+
BTU/HR [†]	1926

KEY

D	Door	R	Refrigerator	
L	Lid	REF	Refrigerator	
H	Half Door	F	Freezer	
FD	Full Door	FRZ	Freezer	
SD	Solid Door	DUAL	REF/FRZ Combo	
GD	Glass Door	DR	Drawer	

	Elevation	Right	Plan	3D	Back
KCL					

(†)Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). (►) Product capacity is calculated based on standard industry figures. (★) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.

VER. 4/18/2023